Proxima Ultralight DS1 Projector
Technical and Functional Specifications

Computer Compatibility	• IBM PC, PS/2, Pentium and compatibles
	• Apple Macintosh, Power Macintosh and PowerBook families
Video Compatibility	• NTSC, PAL, SECAM, NTSC 4.43
Input Sources	• 1 computer 1 video 1 S-video 2 audio
H-Sync Range	• 15-60 kHz
V-Sync Range	• 50-85 Hz
Brightness	• 600 ANSI lumens peak
Contrast Ratio	• 200:1 ANSI; 250:1 full-on, full-off
Display Technology	• Single-chip Digital Light Processing (DLP™)
Resolution	• SVGA (800 x 600)
Resolutions Supported	• VGA (640 x 480, AccuBlend™) SVGA (800 x 600) XGA (1024 x 768, AccuBlend™)
Keystone Correction	• 11.7 - 15.0 degrees
Number of Colors	• 16.7 million
Image Size (Diagonal)	• 2 ft (0.6 m) to 25 ft (7.6 m)
Lens	• Manual zoom lens 1.3:1 ratio Focal length: 2.75 mm-35.75 mm, f/3.0
Projection Distance (From Screen)	• 4 ft (1.2 m) to 39 ft (12 m)
Lamp	• 270 watt metal halide
	• Lamp life: 1000 hours
Audio	• 2-watt monaural speaker
Remote Control	• Proxima Laser F/X™ remote control with laser pointer
Approvals	• FCC Class A, UL, C-UL, CE
Power Consumption	• 380 watts
Power Requirements	• Auto switching 100-120 VAC, 220-240 VAC at 50/60 Hz
Operating Temperature (Sea Level)	• 41°-95°F (5-35°C)
Weight	• 9.9 lb (4.5 kg)
Dimensions	• 9.2 in. W x 12.8 in. L x 4.7 in. H
	• 23.4 cm W x 32.5 cm L x 12.0 cm H
Projection Method	• front/rear, desktop/ceiling
On-screen Menu Languages	• English, Japanese, German, French, Italian, Spanish, Swedish
Audible Noise	• < 46 db
Warranty	• Two years on parts and labor (excluding lamp)

(1) Available as a free upgrade July 1998

Copyright © 1997-2004 InFocus Corporation.
All Rights Reserved.